



**sunpro**<sup>®</sup>

*continuous gas boosted solar specifications*

**thinkefficient**

*one of the most environmentally friendly domestic hot water solutions available*

**thinkinnovation**

*part of Australia's most highly awarded range of environmental water heaters*



**thinkhotwater**

**1300 365 116**

[www.dux.com.au](http://www.dux.com.au)

# sunpro<sup>®</sup> solar gas continuous

## Why you should choose a Dux Sunpro<sup>®</sup> solar gas continuous system

- Gas boosted solar is one of the most environmentally friendly domestic hot water solutions available
- Next generation split system design with the tank on the ground
- High performance black chrome selective surface collectors as standard
- Thicker 4mm toughened averages glass for increased weather resistance
- Available in a range of tank sizes and panel configurations to suit every home
- Suitable for both LPG and Natural Gas

### Did you know

As a guarantee of performance all Dux<sup>®</sup> solar water heaters are now supplied with a genuine Reliance<sup>®</sup> brand Dux<sup>®</sup> solar tempering valve. These valves have been adjusted to Dux specification to ensure maximum hot water delivery.



### RECs Table – Gas Boosted Systems

OPEN CIRCUIT SYSTEMS		COLLECTORS	RECS ZONE			
			1	2	3	4
250 Litres	Sunpro Gas Boosted	2	42	42	42	35
315 Litres	Sunpro Gas Boosted	2	42	42	42	35
400 Litres	Sunpro Gas Boosted	3	48	47	48	43





Calculations are based on Dux 2AP style collector (This panel may not be suitable for all areas). RECs calculations for electric boosted units are based on Continuous Tariff. REC values are subject to change without notice & are correct at time of printing.

CAPACITY (LITRES)	PEOPLE
250	4-6
315	4-7
400	4-8

Size figures are based on environmental averages which can effect the performance of solar & heat pump heaters. Adult icon can represent dishwasher or washing machine. An adult icon does not represent a spa bath.

SPECIFICATIONS	250 LITRE	250 LITRE	315 LITRE	400 LITRE
Storage capacity (L)	259	259	324	416
Hot water delivery rating (L)	250	250	315	400
BOOST				
Gas Continuous	20L	26L	26L	26L
Gas type	Natural/LPG	Natural/LPG	Natural/LPG	Natural/LPG
Net weight empty (kg)	118	118	133	144
Relief valve pressure (kPa)	1000	1000	1000	1000
TANK DIMENSIONS				
<b>A</b> Tank height (mm)	1444	1444	1754	1703
<b>B</b> Tank diameter (mm)	617	617	617	705
<b>C</b> Tank depth (inc. ENDURANCE) (mm)	832	832	832	920



## Contact Dux for your Hot Water Solutions

Sales: 1300 365 116 Service: 1300 365 115 Web Site: [www.dux.com.au](http://www.dux.com.au)  
 © Dux Manufacturing Limited ABN 19 077 879 844. Lackey Rd, PO Box 209 Moss Vale, NSW 2577  
 The information supplied was correct at time of printing. Specification and materials may change without notice.  
 ® and ™ indicate trademarks of Dux Manufacturing Limited. Dux Manufacturing Limited is part of a publicly listed Australian company.

